



Code: SG SHMBDAP

Finish: Chrome

Faceplate Diameter: 155mm depressed plate

Body: Cast Brass

Mixer Barrel Diameter: 54mm

Divertor barrel diameter: 25.5mm

Centre to centre (mixer to diverter): 65mm

Water Inlet: 1/2" BSP Female

Male Male ball valve nipple (Cold Flow Control)

Male Male nipple with one way valve (Hot)

Water Outlet: 3/4" BSP Female (upper and lower)

Divertor: Auto-lockable

Operation: Pull to divert, Turn to lock

Default Outlet: Lower 3/4" BSP Female

Installation: Screwed to back board

Backset: Minimum: 50mm

Maximum: 70mm

Requires hole in back board to clear base of diverter (Dia. 45mm, Depth 15mm)

Minimum Hole Size: 106 x 55mm

Cartridge: 45K Plus Rasied base

Flow Control: Ball valve on cold inlet for unequal pressure systems

Max Flow: Hot @ 35kPa = 12 litres/min

Aquatica Warranty

Aquatica NZ Limited offer the following warranty periods on its range of tapware from the date of purchase.

Residential Use

- Tapware - 5 year warranty
- Handshowers, Shower Roses – 2 year warranty
- Pull-out Sprays and spray heads on Sink Mixer Coils – 2 year warranty
- Kmercial tapware – 2 year warranty

Commercial Use

- Tapware - 1 year warranty
- Handshowers, Shower Roses – 1 year warranty
- Pull-out Sprays and spray heads on Sink Mixer Coils – 1 year warranty

Only high quality workmanship and materials have been used in the manufacture of Aquatica's tapware. If any workmanship or material is proven faulty during the warranty period, Aquatica NZ Limited will, at its own cost or option, repair or replace the faulty product.

The warranty is transferable but the original proof of purchase from an authorised Aquatica distributor is required for all claims.

Aquatica's liability will not extend to damage caused by reasonably foreseeable loss such as inappropriate materials in a wet area ie. floating wooden floors.

Waterlines to tapware incorporating a ceramic cartridge or ceramic disc mechanism should have an inline strainer or filter fitted. Absence of these may void the warranty.

Any suspected defect must be notified to Aquatica as soon as possible after discovery. All repair work must be performed by a plumber who has received authorisation from Aquatica prior to proceeding with the work. Aquatica may immediately authorise repair work to be undertaken, however, this is not necessarily acceptance of liability.

Aquatica guarantee that the tapware will be able to handle temperatures up to a maximum of 80°C.

Water pressure up to 1000 kPa is the maximum limit for the tapware. Above this the warranty will become void.

Serial numbers or tags should not be removed from the products as they are essential in establishing warranty.

Aquatica NZ Limited

9 Saunders Place,
Avondale, Auckland.

Tel: 09-828 2068,

Fax: 09-828 2069

Email: info@aquatica.co.nz

or visit our website:

www.aquatica.co.nz

© copyright Aquatica 2016

Suitable for low/unequal & mains pressure systems

Recommended Operational Pressure Range: 35 - 600 kPa

Maximum Operating Temp: 70°C Never to Exceed: 1000 kPa

No WELS rating required